

# Safety data sheet

according to 1907/2006/EC, Article 31

Page 1/8

Printing date 22.01.2020

Revision: 22.01.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **STALOC 2S78**

UFI: 5661-H0VC-T009-8D3H

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Adhesives

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

Stankovsky Industrieprodukte Handels GmbH  
Flachenuergutstraße 8  
4020 Linz  
AUSTRIA  
Tel.: +43 732 221877  
e-Mail: office@staloc.com  
www.staloc.com

Further information obtainable from: Product safety department

1.4 Emergency telephone number: EU emergency phone number: 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
STOT SE 3 H335 May cause respiratory irritation.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS07

Signal word Warning

#### Hazard-determining components of labelling:

2-hydroxyethyl methacrylate  
acrylic acid  
tert-butyl hydroperoxide

#### Hazard statements

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 2/8

Printing date 22.01.2020

Revision: 22.01.2020

**Trade name: STALOC 2S78**

(Contd. of page 1)

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves / eye protection / face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl methacrylate ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	>10-≤25%
CAS: 41637-38-1	poly(oxy-1,2-ethanediyl), α,α'-[(1-methylethylidene)di-4,1-phenylene]bis[ω-[(2-methyl-1-oxo-2-propen-1-yl)oxy]- Aquatic Chronic 4, H413	>2.5-≤10%
CAS: 79-10-7 EINECS: 201-177-9 Index number: 607-061-00-8	acrylic acid ⚠ Flam. Liq. 3, H226; ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 1 %	≥1-<2.5%
CAS: 75-91-2 EINECS: 200-915-7 Index number: 617-023-00-2	tert-butyl hydroperoxide ⚠ Flam. Liq. 3, H226; Self-react. C, H242; ⚠ Acute Tox. 3, H311; Acute Tox. 2, H330; ⚠ Muta. 2, H341; ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.25-<1%
CAS: 80-15-9 EINECS: 201-254-7 Index number: 617-002-00-8	α,α -dimethylbenzyl hydroperoxide ⚠ Org. Perox. E, H242; ⚠ Acute Tox. 3, H331; ⚠ STOT RE 2, H373; ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 % Skin Irrit. 2; H315: 3 % ≤ C < 10 % Eye Dam. 1; H318: C ≥ 3 % Eye Irrit. 2; H319: 1 % ≤ C < 3 % STOT SE 3; H335: C ≥ 10 %	≥0.25-<1%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General information:** Immediately remove any clothing soiled by the product.

#### After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 3/8

Printing date 22.01.2020

Revision: 22.01.2020

Trade name: STALOC 2S78

(Contd. of page 2)

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

### 5.3 Advice for firefighters

**Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures** Not required.

**6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

**Information about fire - and explosion protection:** No special measures required.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Keep container tightly sealed.

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see item 7.

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

##### 79-10-7 acrylic acid

IOELV	Short-term value: 59* mg/m <sup>3</sup> , 20* ppm Long-term value: 29 mg/m <sup>3</sup> , 10 ppm *reference period of 1 minute
-------	--

**Additional information:** The lists valid during the making were used as basis.

### 8.2 Exposure controls

**Personal protective equipment:**

**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.01.2020

Revision: 22.01.2020

**Trade name: STALOC 2S78**

(Contd. of page 3)

Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	Green
<b>Odour:</b>	Pungent
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not determined.

**Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	Undetermined.

**Flash point:** >100 °C

**Flammability (solid, gas):** Not applicable.

**Decomposition temperature:** Not determined.

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Product does not present an explosion hazard.

**Explosion limits:**

<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.

**Vapour pressure:** Not determined.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 5/8

Printing date 22.01.2020

Revision: 22.01.2020

Trade name: STALOC 2S78

(Contd. of page 4)

· <b>Density at 20 °C:</b>	1.1 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C:</b>	3,500 mPas
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Solids content:</b>	0.0 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· <b>LD/LC50 values relevant for classification:</b>		
<b>868-77-9 2-hydroxyethyl methacrylate</b>		
Oral	LD50	5,050 mg/kg (rat)
<b>79-10-7 acrylic acid</b>		
Oral	LD50	250 mg/kg (rat)
Dermal	LD50	280 mg/kg (rabbit)
<b>75-91-2 tert-butyl hydroperoxide</b>		
Oral	LD50	406 mg/kg (rat)
Dermal	LD50	460 mg/kg (rabbit)
<b>80-15-9 α,α -dimethylbenzyl hydroperoxide</b>		
Oral	LD50	382 mg/kg (rat)
Dermal	LD50	500 mg/kg (rat)
Inhalative	LC50/4 h	220 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 6/8

Printing date 22.01.2020

Revision: 22.01.2020

Trade name: STALOC 2S78

(Contd. of page 5)

- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· <b>14.1 UN-Number</b>	
· <b>ADR, ADN, IMDG, IATA</b>	not regulated
· <b>14.2 UN proper shipping name</b>	
· <b>ADR, ADN, IMDG, IATA</b>	not regulated
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR, ADN, IMDG, IATA</b>	
· <b>Class</b>	not regulated
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	not regulated
· <b>14.5 Environmental hazards:</b>	Not applicable.

(Contd. on page 7)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 22.01.2020

Revision: 22.01.2020

**Trade name: STALOC 2S78**

(Contd. of page 6)

· <b>14.6 Special precautions for user</b>	Not applicable.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	not regulated

## SECTION 15: Regulatory information

### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### · Directive 2012/18/EU

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H226 Flammable liquid and vapour.  
 H242 Heating may cause a fire.  
 H302 Harmful if swallowed.  
 H311 Toxic in contact with skin.  
 H312 Harmful in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H330 Fatal if inhaled.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H341 Suspected of causing genetic defects.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H411 Toxic to aquatic life with long lasting effects.  
 H413 May cause long lasting harmful effects to aquatic life.

· **Department issuing SDS:** Product safety department

· **Contact:** Hr Stankovsky

### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Self-react. C: Self-reactive substances and mixtures – Type C/D  
 Org. Perox. E: Organic peroxides – Type E/F  
 Acute Tox. 4: Acute toxicity - oral – Category 4  
 Acute Tox. 3: Acute toxicity - dermal – Category 3  
 Acute Tox. 2: Acute toxicity - inhalation – Category 2  
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A  
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 8/8

Printing date 22.01.2020

Revision: 22.01.2020

**Trade name: STALOC 2S78**

(Contd. of page 7)

Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
Muta. 2: Germ cell mutagenicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4