

TECHNICAL DATASHEET

STALOC KORROTECH

Anticorrosive wax spray

PRODUCT DESCRIPTION

STALOC Korrotech anticorrosive serves as a wax-like conservation of machines, tools, moulds, fixtures as well as other surfaces. The product applies a viscous, ductile and water repellent film with excellent anti-corrosive effect.

The dripping point of the dry substance is over 100°C, which means that the product can be used in warmer areas (e.g. engine compartments) without dripping.

APPLICATION

Empfohlene Vorgehensweise in der Anwendung, weitere Hinweise im Sicherheitsdatenblatt.

Clean, degrease and dry surfaces. Remove rust from surface. Shake can well before use. Spray STALOC Korrotech onto the substrate and provide for enough drying time. Hold can upright when you spray. Does not harm rubber or plastics, nevertheless STALOC recommends testing of the product before use in non-visible areas. Do not use for painted, decorative surfaces as the paint may result in being dull. When applied onto an engine or in the engine compartment, make sure the surface is cold and dry before application.

TECHNICAL PROPERTIES

ATTRIBUTE	UNIT	SPECIFICATION
Dropping point DIN 51801		~ 100°C
Salt spray test DIN 50021 (40µ)	h	240
Humidity test DIN 50017 (40µ)	h	240
Working temperature	°C	+15 bis +30°C

ATTENTION: Content of the can may freeze. Store at room temperature.

SAFETY INFORMATION

Please send your request for the latest version of the material safety data sheet (MSDS).

PACKAGING / VOLUME

400 ml 520 3e à 12 pcs. per box

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 04.05.2012



call STALOC



www.staloc.com

