

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 1/8

Printing date 22.01.2020

Revision: 14.03.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **STALOC MOS 2 CONTACT SPRAY SQ-440, 400 ml**

Article number: 104408915

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Lubricant

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Stankovsky Industrieprodukte Handels GmbH  
 Flachenauergutstraße 8  
 4020 Linz  
 AUSTRIA  
 Tel.: +43 732 221877  
 e-Mail: office@staloc.com  
 www.staloc.com

Further information obtainable from: Product safety department

1.4 Emergency telephone number: EU emergency phone number: 112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

|                   |           |  |
|-------------------|-----------|--|
| Aerosol 1         | H222-H229 | Extremely flammable aerosol. Pressurised container: May burst if heated. |
| Skin Irrit. 2     | H315      | Causes skin irritation.  |
| STOT SE 3         | H336      | May cause drowsiness or dizziness.                                       |
| Asp. Tox. 1       | H304      | May be fatal if swallowed and enters airways.                            |
| Aquatic Chronic 2 | H411      | Toxic to aquatic life with long lasting effects.                         |

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



Signal word Danger

##### Hazard-determining components of labelling:

Kerosine (petroleum), hydrodesulfurized

##### Hazard statements

|           |  |
|-----------|--|
| H222-H229 | Extremely flammable aerosol. Pressurised container: May burst if heated. |
| H315      | Causes skin irritation.  |
| H336      | May cause drowsiness or dizziness.                                       |
| H411      | Toxic to aquatic life with long lasting effects.                         |

##### Precautionary statements

|      |   |
|------|---|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children.  |
| P103 | Read label before use.  |

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 2/8

Printing date 22.01.2020

Revision: 14.03.2018

**Trade name: STALOC MOS 2 CONTACT SPRAY SQ-440, 400 ml**

(Contd. of page 1)

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

| Dangerous components:  |   |           |
|--|---|-----------|
| CAS: 64742-81-0<br>EINECS: 265-184-9<br>Index number: 649-423-00-8 | Kerosine (petroleum), hydrodesulfurized<br>⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 | >25-≤50%  |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Index number: 601-003-00-5    | propane<br>⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280  | >2.5-≤10% |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Index number: 601-004-00-0   | butane, pure<br>⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280   | >2.5-≤10% |
| CAS: 124-38-9<br>EINECS: 204-696-9                                 | carbon dioxide<br>substance with a Community workplace exposure limit   | >2.5-≤10% |

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General information:** Immediately remove any clothing soiled by the product.

**After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

### 5.3 Advice for firefighters

**Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 3/8

Printing date 22.01.2020

Revision: 14.03.2018

**Trade name: STALOC MOS 2 CONTACT SPRAY SQ-440, 400 ml**

(Contd. of page 2)

### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

### Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Keep container tightly sealed.

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

**Additional information about design of technical facilities:** No further data; see item 7.

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

124-38-9 carbon dioxide

IOELV | Long-term value: 9000 mg/m<sup>3</sup>, 5000 ppm

**Additional information:** The lists valid during the making were used as basis.

### 8.2 Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Protection of hands:



Protective gloves

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 4/8

Printing date 22.01.2020

Revision: 14.03.2018

**Trade name: STALOC MOS 2 CONTACT SPRAY SQ-440, 400 ml**

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Not required.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

#### Appearance:

|                  |                 |
|------------------|-----------------|
| Form:            | Aerosol         |
| Colour:          | Light grey      |
| Odour:           | Characteristic  |
| Odour threshold: | Not determined. |

pH-value: Not determined.

#### Change in condition

|  |                             |
|--|-----------------------------|
| Melting point/freezing point:            | Undetermined.               |
| Initial boiling point and boiling range: | Not applicable, as aerosol. |

Flash point: -60 °C

Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

#### Explosion limits:

|        |           |
|--------|-----------|
| Lower: | 0.6 Vol % |
| Upper: | 6.5 Vol % |

Vapour pressure at 20 °C: 6,000 hPa

Density at 20 °C: 0.82 g/cm<sup>3</sup>

Relative density: Not determined.

Vapour density: Not determined.

Evaporation rate: Not applicable.

#### Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.

#### Viscosity:

|            |                 |
|------------|-----------------|
| Dynamic:   | Not determined. |
| Kinematic: | Not determined. |

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 5/8

Printing date 22.01.2020

Revision: 14.03.2018

Trade name: **STALOC MOS 2 CONTACT SPRAY SQ-440, 400 ml**

(Contd. of page 4)

|                              |  |
|------------------------------|--|
| <b>Solvent content:</b>      |  |
| Organic solvents:            | 50.3 %                                     |
| VOC (EC)                     | 412.5 g/l                                  |
| VOC (EC)                     | 48.50 %                                    |
| <b>Solids content:</b>       |  |
|                              | 94.0 %                                     |
| <b>9.2 Other information</b> | No further relevant information available. |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

|                       |          |                |
|-----------------------|----------|----------------|
| 106-97-8 butane, pure |          |                |
| Inhalative            | LC50/4 h | 658 mg/l (rat) |

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxic effects:**
- **Remark:** Toxic for fish

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 6/8

Printing date 22.01.2020

Revision: 14.03.2018

**Trade name: STALOC MOS 2 CONTACT SPRAY SQ-440, 400 ml**

(Contd. of page 5)

**Additional ecological information:**

**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
 Also poisonous for fish and plankton in water bodies.  
 Toxic for aquatic organisms

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations



**13.1 Waste treatment methods**

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

|   |  |
|---|--|
| <b>14.1 UN-Number</b>   |  |
| <b>ADR, IMDG, IATA</b>  | UN1950   |
| <b>14.2 UN proper shipping name</b>   |  |
| <b>ADR</b>  | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS                             |
| <b>IMDG</b>   | AEROSOLS (Kerosine (petroleum), hydrodesulfurized), MARINE POLLUTANT |
| <b>IATA</b>   | AEROSOLS, flammable  |
| <b>14.3 Transport hazard class(es)</b>  |  |
| <b>ADR</b>  |  |
|  |  |
| <b>Class</b>  | 2 5F Gases.  |
| <b>Label</b>  | 2.1  |
| <b>IMDG</b>   |  |
|  |  |
| <b>Class</b>  | 2.1  |
| <b>Label</b>  | 2.1  |

(Contd. on page 7)


**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 22.01.2020

Revision: 14.03.2018

**Trade name: STALOC MOS 2 CONTACT SPRAY SQ-440, 400 ml**

(Contd. of page 6)

|  |  |
|--|--|
| · <b>IATA</b>  |  |
|               |  |
| · <b>Class</b>   | 2.1  |
| · <b>Label</b>   | 2.1  |
| · <b>14.4 Packing group</b>  |  |
| · <b>ADR, IMDG, IATA</b>   | not regulated  |
| · <b>14.5 Environmental hazards:</b>   |  |
| Product contains environmentally hazardous substances: Kerosine (petroleum), hydrodesulfurized |  |
| · <b>Marine pollutant:</b>   | Symbol (fish and tree)   |
| · <b>Special marking (ADR):</b>  | Symbol (fish and tree)   |
| · <b>14.6 Special precautions for user</b>   |  |
| · <b>Danger code (Kemler):</b>   | Warning: Gases.  |
| · <b>EMS Number:</b>   | -  |
| · <b>Stowage Code</b>  | F-D,S-U  |
| · <b>Segregation Code</b>  | SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.<br>SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.<br>For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.<br>For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>               |  |
| Not applicable.  |  |
| · <b>Transport/Additional information:</b>   |  |
| · <b>ADR</b>   |  |
| · <b>Limited quantities (LQ)</b>   | 1L   |
| · <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity   |
| · <b>Transport category</b>  | 2  |
| · <b>Tunnel restriction code</b>   | D  |
| · <b>IMDG</b>  |  |
| · <b>Limited quantities (LQ)</b>   | 1L   |
| · <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity   |
| · <b>UN "Model Regulation":</b>  | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS   |

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Page 8/8

Printing date 22.01.2020

Revision: 14.03.2018

Trade name: **STALOC MOS 2 CONTACT SPRAY SQ-440, 400 ml**

(Contd. of page 7)

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

##### Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Department issuing SDS:** Product safety department

**Contact:** Hr Stankovsky

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2