

Page 1/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.01.2020 Revision: 28.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: STALOC power foam SQ-250, 500 ml

· Article number: 104408903

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

* Application of the substance / the mixture Cleaning agent/ Cleaner

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Stankovsky Industrieprodukte Handels GmbH Flachenauergutstraße 8 4020 Linz AUSTRIA

Tel.: +43 732 221877 e-Mail: office@staloc.com www.staloc.com

Further information obtainable from: Product safety department

1.4 Emergency telephone number: EU emergency phone number: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





Signal word Danger

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

(Contd. on page 2)



Printing date 22.01.2020 Revision: 28.01.2019

Trade name: STALOC power foam SQ-250, 500 ml

(Contd. of page 1)

Page 2/8

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0	propan-2-ol Flam. Liq. 2, H225; (*) Eye Irrit. 2, H319; STOT SE 3, H336	>10-<20%		
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane Flam. Gas 1, H220	>2.5-≤10%		
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0	isobutane The property is a second of the property is a s	>2.5-≤10%		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane, pure Flam. Gas 1, H220	>2.5-≤10%		
CAS: 1336-21-6 EINECS: 215-647-6 Index number: 007-001-01-2	ammonia Skin Corr. 1B, H314; ♦ Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ♦ STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	≥0.25-<1%		
Regulation (EC) No 64	8/2004 on detergents / Labelling for contents			
aliphatic hydrocarbons		≥5 - <15%		
anionic surfactants		<5%		
perfumes				

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- * After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- * After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- * 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- * Protective equipment: No special measures required.



Printing date 22.01.2020 Revision: 28.01.2019

Trade name: STALOC power foam SQ-250, 500 ml

(Contd. of page 2)

Page 3/8

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- * Additional information about design of technical facilities: No further data; see item 7.
- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection: Not required.

Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Printing date 22.01.2020 Revision: 28.01.2019

Trade name: STALOC power foam SQ-250, 500 ml

(Contd. of page 3)

Page 4/8

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value at 20 °C:	9.5
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	Not applicable, as aerosol.
Flash point:	-60 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	365 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	2 Vol %
Upper:	12 Vol %
Vapour pressure at 20 °C:	4,000 hPa
Density at 20 °C:	0.9 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.

(Contd. on page 5)



Printing date 22.01.2020 Revision: 28.01.2019

Trade name: STALOC power foam SQ-250, 500 ml

(Contd. of page 4)

Page 5/8

Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	25.0 %
VOC (EC)	270.0 g/l
VOC (EC)	30.00 %
Solids content:	0.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- *Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- * 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- * 10.5 Incompatible materials: No further relevant information available.
- * 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:				
67-63-0 propan-2-ol				
Oral	LD50	5,045 mg/kg (rat)		
Dermal	LD50	12,800 mg/kg (rabbit)		
Inhalative	LC50/4 h	30 mg/l (rat)		
106-97-8 butane, pure				
Inhalative LC50/4 h 658 mg/l (rat)				

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- * Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- * Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.



Printing date 22.01.2020 Revision: 28.01.2019

Trade name: STALOC power foam SQ-250, 500 ml

(Contd. of page 5)

Page 6/8

- * 12.2 Persistence and degradability No further relevant information available.
- * 12.3 Bioaccumulative potential No further relevant information available.
- * 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number		
ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	
14.3 Transport hazard class(es)		

ADR



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class 2.1 Label 2.1

14.4 Packing group

ADR, IMDG, IATA not regulated

* **14.5 Environmental hazards:** Not applicable.

* 14.6 Special precautions for user Warning: Gases.

(Contd. on page 7)



Printing date 22.01.2020 Revision: 28.01.2019

Trade name: STALOC power foam SQ-250, 500 ml

(Contd. of page 6)

Page 7/8

Danger code (Kemler):

* **EMS Number:** F-D,S-U

*Segregation groups Ammonium compounds, alkalis
*Stowage Code SW1 Protected from sources of heat.

SW2 Clear of living quarters.

* Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for

division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

Transport/Additional information:

· ADR

Limited quantities (LQ)

Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

Transport category 2
Tunnel restriction code

·IMDG

Limited quantities (LQ)

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

* UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- * Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.



Printing date 22.01.2020 Revision: 28.01.2019

Trade name: STALOC power foam SQ-250, 500 ml

(Contd. of page 7)

Page 8/8

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Product safety department

Contact: Hr Stankovsky

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2