

## TECHNICAL DATASHEET

**STALOC ADHESIVE GREASE SPRAY**

SQ-430

**PRODUCT DESCRIPTION**

STALOC adhesive grease spray is a transparent high performance lubrication grease used to grease bearings, brackets, gears, chain drives, wheels, worm drives, etc.

In addition, it can be used to lubricate all kinds of engine parts, precision parts, joints, hinges and connectors. Provided by its excellent creeping characteristics the product can be used even in areas that are difficult to access.

Can be used also for door closers, door hinges, slide bars, slide rails, levers, rods, pivot arms, etc.

**APPLICATION**

Recommended application – further information can be found in the material safety data sheet

Clean and degrease surface before application of STALOC adhesive grease spray. Shake well before use. Spray from a distance of 20-30cm onto the substrate. The immediate evaporation of the solvent provides for a perfect adhesion of the lubricant.

**TECHNICAL PROPERTIES**

ATTRIBUTE	UNIT	SPECIFICATION
colour		transparent
chemical basis		lubricant based on synthetic oils, mineral oils and adhesion agents
temperature resistance	°C	-20°C to +180°C (short-term up to +230°C)

Eliminates moisture and water, removes rust, excellent creep and adhering characteristics, no centrifuge on rotating elements. Long-term penetration. Resistant against slight acids and alkali. Does not contain silicone, resin or acids. Not suitable for food industry.

**SAFETY INFORMATION**

Please send your request for the latest version of the material safety data sheet (MSDS).

**PACKAGING / VOLUME**

400 ml 520 3e / 12 pcs. per box

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 04.05.2012



call STALOC



[www.staloc.com](http://www.staloc.com)



[WWW.STALOC.COM](http://WWW.STALOC.COM)