

TECHNICAL DATASHEET

STALOC KORROTECH 1000 GREASE-FREE LUBRICANT

SQ-1001

PRODUCT DESCRIPTION

STALOC KORROTECH 1000 grease-free lubricant is composed from pure raw materials in order to ensure the highest possible product quality. It eliminates moisture from electric and electronic devices, creeps and displaces corrosion and moisture. The product offers grease-free and clean lubrication. It contains vapour corrosion inhibitors, thereby ensuring an active corrosion protection. STALOC KORROTECH 1000 does not contain oils or other oil-ingredients.

Main area of application is the wood-working industry, where the product is used as a gliding lubricant. It also acts as an oil- and wax-free anti-corrosive for a temporary inhouse conservation.

APPLICATION

Recommended application – further information can be found in the material safety data sheet.

If STALOC KORROTECH 1000 grease-free lubricant is used for cleaning, the affected parts must be intensely sprayed and/or washed up and wiped with a cloth. Spray STALOC KORROTECH 1000 onto the substrate from a distance of 25-30 cm.

Highest effectiveness directly after application!

GENERAL PROPERTIES

- excellent mechanical and thermal stability
- very good penetration
- eliminates moisture
- good cleaning effect
- excellent corrosion protection due to VCI additives
- does not harm paint or plastics
- excellent handling due to 360° spray valve

TECHNICAL PROPERTIES

ATTRIBUTE	UNIT	SPECIFICATION
colour		transparent
basis		Isoparaffin
active agent		Approx. 99% w/w
temperature resistance	°C	-40°C to 100°C
application temperature	°C	+15°C to 35°C
Odour		wintergreen
density at 20°C	g/ml	0,810 – 0,820 g/ml
resistant against		weak acids and bases atmospheric exposure
shelf life at +25°C	years	10 years

SAFETY INFORMATION

Please send your request for the latest version of the material safety data sheet (MSDS).

PACKAGING / VOLUME

400 ml 520 3e à 12 pcs. per box

5 l / 20 l / 180 l container

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 04.05.2012



call STALOC



www.staloc.com



WWW.STALOC.COM