

TECHNICAL DATASHEET

STALOC CONTACT SPRAY WITH MoS₂

SQ-440

PRODUCT DESCRIPTION

STALOC contact spray with MoS₂ improves ignitability, undercuts and eliminates moisture. Cleans and maintains electrical contacts, fuses, cable connectors, etc. Prevents oxidation. Facilitates current flow. Prevents creep flows and voltage loss. Protects and lubricates.

APPLICATION

Recommended application – further information can be found in the material safety data sheet

Spray STALOC contact spray with MoS₂ onto the desired area and provide for penetration time. Repeat treatment if necessary.

TECHNICAL PROPERTIES

ATTRIBUTE	UNIT	SPECIFICATION
colour		off-white
basis		based on mineral oils with added additives, anticorrosives and MoS ₂

Silicone-free. Does not harm paint, technical textiles or rubber. Cover plastic parts or test before use.

SAFETY INFORMATION

Please send your request for the latest version of the material safety data sheet (MSDS).

PACKAGING / VOLUME

400 ml 520 3e / 12 pcs. per box

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 04.05.2012

