

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **STALOC 5S11 Pipe thread sealant with PTFE, low-strength, 50 / 250 ml**

Article number: 5S11

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Adhesives

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Stankovsky Industrieprodukte Handels GmbH  
Flachenauergutstraße 8  
4020 Linz  
AUSTRIA  
Tel.: +43 732 221877  
e-Mail: office@staloc.com  
www.staloc.com

Further information obtainable from: Product safety department

#### 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS07

Signal word Warning

##### Hazard-determining components of labelling:

methacrylic acid, monoester with propane-1,2-diol

##### Hazard statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

##### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves / eye protection / face protection.  
P264 Wash thoroughly after handling.

(Contd. on page 2)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC 5S11 Pipe thread sealant with PTFE, low-strength, 50 / 250 ml**

(Contd. of page 1)

- P272 Contaminated work clothing should not be allowed out of the workplace.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 Specific treatment (see on this label).  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

- PBT:** Not applicable.  
**vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

| Dangerous components:  |  |           |
|--|--|-----------|
| CAS: 27813-02-1<br>EINECS: 248-666-3<br>Reg.nr.: 01-2119490226-37-XXXX | methacrylic acid, monoester with propane-1,2-diol<br>⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317  | >2.5-<10% |
| CAS: 80-15-9<br>EINECS: 201-254-7                                      | α,α -dimethylbenzyl hydroperoxide<br>⚠ Org. Perox. C, H242; ⚠ Acute Tox. 3, H331; ⚠ STOT RE 2, H373; ⚠ Skin Corr. 1A, H314; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335<br>Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 %<br>Skin Irrit. 2; H315: 3 % ≤ C < 10 %<br>Eye Dam. 1; H318: C ≥ 3 %<br>Eye Irrit. 2; H319: 1 % ≤ C < 3 %<br>STOT SE 3; H335: C < 10 % | ≥1-<2.5%  |

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General information:** Immediately remove any clothing soiled by the product.

#### After inhalation:

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

### 5.3 Advice for firefighters

**Protective equipment:** No special measures required.

(Contd. on page 3)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC 5S11 Pipe thread sealant with PTFE, low-strength, 50 / 250 ml**

(Contd. of page 2)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**  
**Storage:**  
**Requirements to be met by storerooms and receptacles:** No special requirements.  
**Information about storage in one common storage facility:** Not required.  
**Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC 5S11 Pipe thread sealant with PTFE, low-strength, 50 / 250 ml**

(Contd. of page 3)

### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

### Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

#### Appearance:

|                  |                 |
|------------------|-----------------|
| Form:            | Viscous         |
| Colour:          | White           |
| Odour:           | Characteristic  |
| Odour threshold: | Not determined. |

pH-value: Not determined.

#### Change in condition

|  |               |
|--|---------------|
| Melting point/freezing point:            | Undetermined. |
| Initial boiling point and boiling range: | Undetermined. |

Flash point: >100 °C

Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

#### Explosion limits:

|        |                 |
|--------|-----------------|
| Lower: | Not determined. |
| Upper: | Not determined. |

Vapour pressure: Not determined.

Density at 20 °C: 1.01 g/cm<sup>3</sup>

Relative density: Not determined.

Vapour density: Not determined.

Evaporation rate: Not determined.

#### Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.

#### Viscosity:

|                   |                 |
|-------------------|-----------------|
| Dynamic at 20 °C: | 57,500 mPas     |
| Kinematic:        | Not determined. |

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC 5S11 Pipe thread sealant with PTFE, low-strength, 50 / 250 ml**

(Contd. of page 4)

|                              |  |
|------------------------------|--|
| <b>Solvent content:</b>      |  |
| <b>Solids content:</b>       | 75.0 %                                     |
| <b>9.2 Other information</b> | No further relevant information available. |

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

|   |          |                 |
|---|----------|-----------------|
| <b>LD/LC50 values relevant for classification:</b>    |          |                 |
| 80-15-9 $\alpha,\alpha$ -dimethylbenzyl hydroperoxide |          |                 |
| Oral  | LD50     | 382 mg/kg (rat) |
| Dermal  | LD50     | 500 mg/kg (rat) |
| Inhalative  | LC50/4 h | 220 mg/l (rat)  |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC 5S11 Pipe thread sealant with PTFE, low-strength, 50 / 250 ml**

(Contd. of page 5)

### 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

### Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

|  |                 |
|--|-----------------|
| · <b>14.1 UN-Number</b>  |                 |
| · <b>ADR, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>14.2 UN proper shipping name</b>  |                 |
| · <b>ADR, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>14.3 Transport hazard class(es)</b>   |                 |
| · <b>ADR, ADN, IMDG, IATA</b>  |                 |
| · <b>Class</b>   | not regulated   |
| · <b>14.4 Packing group</b>  |                 |
| · <b>ADR, IMDG, IATA</b>   | not regulated   |
| · <b>14.5 Environmental hazards:</b>   | Not applicable. |
| · <b>14.6 Special precautions for user</b>                                       | Not applicable. |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b> | Not applicable. |
| · <b>UN "Model Regulation":</b>  | not regulated   |

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

(Contd. on page 7)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC 5S11 Pipe thread sealant with PTFE, low-strength, 50 / 250 ml**

(Contd. of page 6)

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

**Department issuing SDS:** Product safety department

**Contact:** Hr Stankovsky

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. C: Organic peroxides – Type C/D

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2