

TECHNICAL DATASHEET

STALOC ACTIVATOR FOR INSTANT ADHESIVES

Spray

PRODUCT DESCRIPTION

STALOC Activator for Instant Adhesives is used to activate STALOC Instant Adhesives. The curing of the adhesive is significantly accelerated, especially with large layer thicknesses. STALOC Activator for Instant Adhesives is also used with inactive materials and unfavourable processing conditions.

APPLICATION

Recommended application – further information can be found in the material safety data sheet

Application temperature is 10 to 30°C. Shake before using. STALOC Activator for Instant Adhesives must be applied on both bonding partners and then the Instant Adhesives must be applied. Or apply the Instant Adhesive to the gap, adjust the components and then apply the STALOC Activator for Instant Adhesives.

SAFETY INFORMATION

Please send your request for the latest version of the material safety data sheet (MSDS).

PACKAGING / VOLUME

150ml spray / 6 pcs. per box

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 04.05.2012



Call STALOC



www.staloc.com