

## TECHNICAL DATASHEET

**STALOC QUICKFIX MULTI ADHESIVE**

Universal repair adhesive

**PRODUCT DESCRIPTION**

This newly developed adhesive system combines the capabilities of instant adhesive systems with their quick tack and the gap-bridging provided by 2K adhesive systems such as epoxy, polyurethane or methacrylate. Thus STALOC Quick Fix Multi Adhesive is the ideal product when it comes to small repairs or quick and effective fastenings.

- Bonds metal, plastic, wood, rubber, glass, ceramics, cardboard, leather, PVC, ABS, PC, PBT, rubber, textiles, etc.
- Fixes quickly
- Can be reworked
- Bridges gaps of up to 6mm and can be worked overhead
- Temperature resistance from -20°C to +80°C (short term up to +120°C)
- Working time: 3 min.
- Transparent

**PHYSICAL PROPERTIES (WHEN CURED)**

Tested to ISO 4587

SUBSTRATE	UNIT	SHEAR STRENGTH
Mild Steel	N/mm <sup>2</sup>	19,5
Aluminium	N/mm <sup>2</sup>	6
ABS	N/mm <sup>2</sup>	10,5 (substrate failure)
Plycarbonate	N/mm <sup>2</sup>	10,2 (substrate failure)

**APPLICATION**

Recommended application – further information can be found in the material safety data sheet

The parts to be bonded need to be cleaned and degreased. It is recommended to use STALOC technical cleaners, in order to ensure the best results in terms of adhesion.

**STORAGE**

Recommended storage for optimum shelf life

Store in a cool and dry place, ideally at 7°C – 15°C. Shelf life 9 months.

**SAFETY INFORMATION**

Please send your request for the latest version of the material safety data sheet (MSDS).

**PACKAGING / VOLUME**

10g syringe, incl. 3 mixers / 10 pcs. per box

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 31.07.2017



call STALOC



[www.staloc.com](http://www.staloc.com)

