

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **STALOC HTP Hochleistungsschmierstoff SQ-496, 500 ml**

Article number: 110661211

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Lubricant

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Stankovsky Industrieprodukte Handels GmbH  
Flachenauergutstraße 8  
4020 Linz  
AUSTRIA  
Tel.: +43 732 221877  
e-Mail: office@staloc.com  
www.staloc.com

Further information obtainable from: Product safety department

#### 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS02

Signal word Danger

##### Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated light paraffinic

pentane

Hydrocarbons C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

##### Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC HTP Hochleistungsschmierstoff SQ-496, 500 ml**

(Contd. of page 1)

- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251 Do not pierce or burn, even after use.
- P211 Do not spray on an open flame or other ignition source.
- P273 Avoid release to the environment.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 64742-55-8 EINECS: 265-158-7 Reg.nr.: 01-2119487077-29	Distillates (petroleum), hydrotreated light paraffinic ☠ Asp. Tox. 1, H304	>25-≤50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21xxxx	propane ☠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	>10-≤25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ☠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	>10-≤25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane, pure ☠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	>10-≤25%
CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30	pentane ☠ Flam. Liq. 2, H225; ☠ Asp. Tox. 1, H304; ☠ Aquatic Chronic 2, H411; ☠ STOT SE 3, H336	>10-≤20%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics ☠ Asp. Tox. 1, H304	>10-≤25%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Generally the product does not irritate the skin.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC HTP Hochleistungsschmierstoff SQ-496, 500 ml**

(Contd. of page 2)

### 5.3 Advice for firefighters

**Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling** No special precautions are necessary if used correctly.

### Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Keep container tightly sealed.

**7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

**Additional information about design of technical facilities:** No further data; see item 7.

### Ingredients with limit values that require monitoring at the workplace:

109-66-0 pentane

WEL Long-term value: 1800 mg/m<sup>3</sup>, 600 ppm

**Additional information:** The lists valid during the making were used as basis.

### 8.2 Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.

**Respiratory protection:** Not required.

#### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC HTP Hochleistungsschmierstoff SQ-496, 500 ml**

(Contd. of page 3)

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Not required.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

##### General Information

##### Appearance:

<b>Form:</b>	Aerosol
<b>Colour:</b>	According to product specification
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not determined.

##### Change in condition

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	Not applicable, as aerosol.

**Flash point:** <0 °C

**Flammability (solid, gas):** Not applicable.

**Ignition temperature:** >200 °C

**Decomposition temperature:** Not determined.

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

##### Explosion limits:

<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	10.9 Vol %

**Vapour pressure at 20 °C:** 3,500 hPa

**Density at 20 °C:** 0.7 g/cm<sup>3</sup>

**Relative density** Not determined.

**Vapour density** Not determined.

**Evaporation rate** Not applicable.

##### Solubility in / Miscibility with water:

Not miscible or difficult to mix.

**Partition coefficient: n-octanol/water:** Not determined.

##### Viscosity:

<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.

(Contd. on page 5)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC HTP Hochleistungsschmierstoff SQ-496, 500 ml**

(Contd. of page 4)

<b>Solvent content:</b>	
<b>Organic solvents:</b>	35.0 %
<b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

<b>LD/LC50 values relevant for classification:</b>
106-97-8 butane, pure
Inhalative   LC50/4 h   658 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC HTP Hochleistungsschmierstoff SQ-496, 500 ml**

(Contd. of page 5)

Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**



· **13.1 Waste treatment methods**

· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

· <b>14.1 UN-Number</b>	
· <b>ADR, IMDG, IATA</b>	UN1950
· <b>14.2 UN proper shipping name</b>	
· <b>ADR</b>	1950 AEROSOLS
· <b>IMDG</b>	AEROSOLS
· <b>IATA</b>	AEROSOLS, flammable
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR</b>	
	
· <b>Class</b>	2 5F Gases.
· <b>Label</b>	2.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	2.1 Gases.
· <b>Label</b>	2.1
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	not regulated
· <b>14.5 Environmental hazards:</b>	Not applicable.
· <b>14.6 Special precautions for user</b>	Warning: Gases.
· <b>Hazard identification number (Kemler code):</b>	-
· <b>EMS Number:</b>	F-D,S-U
· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre:

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC HTP Hochleistungsschmierstoff SQ-496, 500 ml**

(Contd. of page 6)

	Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

## SECTION 15: Regulatory information

### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### · Directive 2012/18/EU

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P3a FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department

· **Contact:** Hr Stankovsky

### · **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 8)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC HTP Hochleistungsschmierstoff SQ-496, 500 ml**

(Contd. of page 7)

CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Gas 1A: Flammable gases – Category 1A  
Aerosol 1: Aerosols – Category 1  
Press. Gas (Comp.): Gases under pressure – Compressed gas  
Flam. Liq. 2: Flammable liquids – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3