

TECHNICAL DATASHEET

STALOC CHAIN SPRAY WITH MoS_2

SQ-480

PRODUCT DESCRIPTION

STALOC chain spray with MoS_2 is a long-term lubricant for chains, machines, ropes, cables, rolls, bearings, inner bearings, gear drives, worm drives, hinges, precision parts, etc.

The product is suited for reducing friction of moving components. Additionally, it can be used as a lubricant for o-rings, coach springs, frame joints, Bowden cables, etc.

APPLICATION

Recommended application – further information can be found in the material safety data sheet.

Remove contamination from parts that need to be treated. Shake well before use. After use, turn the spray can upside down and spray until tube is free of lubricant.

TECHNICAL PROPERTIES

ATTRIBUTE	UNIT	SPECIFICATION
colour		dark grey
basis		based on mineral oils and synthetic oils, includes anticorrosion additives, adhesion additives and MoS_2
temperature resistance	°C	-30°C to 250°C

- highly resilient, specialised lubricant with excellent adhering characteristics
- very well suited for high compression loads
- for chains, cables, rollers, bolts, bearings, etc.
- does not leach
- displaces moisture
- penetrates and undercuts surface corrosion
- excellent adhesion
- does not run off

SAFETY INFORMATION

Please send your request for the latest version of the material safety data sheet (MSDS).

PACKAGING / VOLUME

400 ml 520 3e à 12 pcs. per box

The information and data in this document are for information purposes only. STALOC cannot take responsibility for the results obtained by a third party, whose methods are not under STALOC control. The determination of the suitability for the user's purpose of any STALOC product is the responsibility of the client. Consequently, STALOC recommends testing of the products before using it for a series application. Moreover, it is the responsibility of the customer to ensure a safe environment for the user. STALOC therefore disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of STALOC products. STALOC cannot be held liable for any consequential or incidental damage resulting from the use of a STALOC product, including lost profits or damages of any other kind. Products or processes mentioned herein might be subject to released or pending patents or licences.

Issued: 04.05.2012



call STALOC



www.staloc.com

