

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **STALOC Zinkspray hell SQ-850, 400 ml**

Article number: 104408907

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Anticorrosion additive

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Stankovsky Industrieprodukte Handels GmbH  
Flachenauergutstraße 8  
4020 Linz  
AUSTRIA  
Tel.: +43 732 221877  
e-Mail: office@staloc.com  
www.staloc.com

Further information obtainable from: Product safety department

#### 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS02

GHS07

GHS09

Signal word Danger

##### Hazard-determining components of labelling:

hydrocarbons, C9, aromatics

acetone

##### Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC Zinkspray hell SQ-850, 400 ml**

(Contd. of page 1)

### Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P251 Do not pierce or burn, even after use.  
P211 Do not spray on an open flame or other ignition source.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear eye protection / face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P405 Store locked up.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

### 2.3 Other hazards

### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-XXXX	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	>25-≤50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	≥20-≤25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	>10-<20%
CAS: 7440-66-6 EINECS: 231-175-3	zinc powder -zinc dust (stabilized) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	>2.5-≤10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	>2.5-<10%
CAS: 7429-90-5 EINECS: 231-072-3	aluminium ⚠ Pyr. Sol. 1, H250; Water-react. 2, H261	>2.5-≤10%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32-xxxx	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<2.5%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Generally the product does not irritate the skin.

(Contd. on page 3)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC Zinkspray hell SQ-850, 400 ml**

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC Zinkspray hell SQ-850, 400 ml**

(Contd. of page 3)

<b>Ingredients with limit values that require monitoring at the workplace:</b>	
<b>115-10-6 dimethyl ether</b>	
WEL	Short-term value: 958 mg/m <sup>3</sup> , 500 ppm Long-term value: 766 mg/m <sup>3</sup> , 400 ppm
<b>67-64-1 acetone</b>	
WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
<b>1330-20-7 xylene</b>	
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
<b>Ingredients with biological limit values:</b>	
<b>1330-20-7 xylene</b>	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

**Additional information:** The lists valid during the making were used as basis.

### 8.2 Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection:



Tightly sealed goggles

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

Trade name: STALOC Zinkspray hell SQ-850, 400 ml

(Contd. of page 4)

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

<b>Form:</b>	Aerosol
<b>Colour:</b>	Silver-coloured
<b>Odour:</b>	Solvent-like
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not determined.

**Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	Not applicable, as aerosol.

**Flash point:** <0 °C

**Flammability (solid, gas):** Not applicable.

**Ignition temperature:** 240 °C

**Decomposition temperature:** Not determined.

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**Explosion limits:**

<b>Lower:</b>	0.7 Vol %
<b>Upper:</b>	26.2 Vol %

**Vapour pressure at 20 °C:** 5,200 hPa

**Density at 20 °C:** 0.865 g/cm<sup>3</sup>

**Relative density** Not determined.

**Vapour density** Not determined.

**Evaporation rate** Not applicable.

**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Partition coefficient: n-octanol/water:** Not determined.

**Viscosity:**

<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.

**Solvent content:**

<b>Organic solvents:</b>	56.0 %
<b>VOC (EC)</b>	484.4 g/l
<b>VOC (EC)</b>	56.00 %

**9.2 Other information**

No further relevant information available.

**SECTION 10: Stability and reactivity**

**10.1 Reactivity** No further relevant information available.

(Contd. on page 6)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC Zinkspray hell SQ-850, 400 ml**

(Contd. of page 5)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

<b>115-10-6 dimethyl ether</b>		
Inhalative	LC50/4 h	308 mg/l (rat)
<b>67-64-1 acetone</b>		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
<b>1330-20-7 xylene</b>		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
<b>1314-13-2 zinc oxide</b>		
Oral	LD50	>5,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC Zinkspray hell SQ-850, 400 ml**

(Contd. of page 6)

Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**




**13.1 Waste treatment methods**

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

<b>14.1 UN-Number</b>	
<b>ADR, IMDG, IATA</b>	UN1950
<b>14.2 UN proper shipping name</b>	
<b>ADR</b>	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
<b>IMDG</b>	AEROSOLS, MARINE POLLUTANT
<b>IATA</b>	AEROSOLS, flammable
<b>14.3 Transport hazard class(es)</b>	
<b>ADR</b>	
	
<b>Class</b>	2.5F Gases.
<b>Label</b>	2.1
<b>IMDG</b>	
	
<b>Class</b>	2.1 Gases.
<b>Label</b>	2.1
<b>IATA</b>	
	
<b>Class</b>	2.1 Gases.
<b>Label</b>	2.1

(Contd. on page 8)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC Zinkspray hell SQ-850, 400 ml**

(Contd. of page 7)

· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	not regulated
· <b>14.5 Environmental hazards:</b> · <b>Marine pollutant:</b> · <b>Special marking (ADR):</b>	Product contains environmentally hazardous substances: hydrocarbons, C9, aromatics Symbol (fish and tree) Symbol (fish and tree)
· <b>14.6 Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>EMS Number:</b> · <b>Stowage Code</b>  · <b>Segregation Code</b>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>  · <b>Transport category</b> · <b>Tunnel restriction code</b>	1L Code: E0 Not permitted as Excepted Quantity 2 D
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

**SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
P3a FLAMMABLE AEROSOLS  
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.01.2023

Revision: 22.12.2022

**Trade name: STALOC Zinkspray hell SQ-850, 400 ml**

(Contd. of page 8)

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H250 Catches fire spontaneously if exposed to air.  
H261 In contact with water releases flammable gases.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

**Department issuing SDS:** Product safety department

**Contact:** Hr Stankovsky

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Gas 1A: Flammable gases – Category 1A  
Aerosol 1: Aerosols – Category 1  
Press. Gas (Comp.): Gases under pressure – Compressed gas  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Pyr. Sol. 1: Pyrophoric solids – Category 1  
Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2